



- ▶ Compact and streamlined design
- ▶ Individual sheave lubrication lines
- ▶ Hydraulic snubber (optional)
- ▶ Eight position swivel lock allowing for 360 degree rotation
- ▶ Hook positioner (optional)

MODEL	CAPACITY	SHEAVE O.D.	# OF SHEAVES	WIRE ROPE (IN.)	A (IN./MM)	B (IN./MM)	C (IN./MM)	D (IN./MM)	WEIGHT (LBS./KG)
D24C110	110	24	3	1-1.125	78.00	1981	70.63	1794	26.50 673 15.50 394 3230 1465
D30C110	110	30	3	1-1.125	85.88	2181	79.50	2019	32.50 826 15.50 394 3300 1497
D30C160	160	30	3	1-1.125	110.50	2807	99.00	2515	33.00 838 20.00 508 6800 3084
D36C160	160	36	3	1-1.125	117.00	2972	105.00	2667	39.00 991 20.00 508 6900 3130
D30D160	160	30	4	1-1.125	110.50	2807	99.00	2515	33.00 838 20.00 508 6900 3130
D36D160	160	36	4	1-1.125	117.00	2972	105.00	2667	39.00 991 20.00 508 7000 3175
D30D175	175	30	4	1-1.250	113.00	2870	100.00	2540	33.00 838 20.00 508 6900 3130
D30E200	200	30	5	1-1.250	120.25	3054	106.00	2692	35.00 889 24.75 629 10000 4536
D36E200	200	36	5	1-1.250	126.25	3207	112.00	2845	39.00 991 24.75 629 11600 5262
D36D265	265	36	4	1-1.250	126.25	3207	112.00	2845	39.00 991 24.75 629 11000 4990
D36E265	265	36	5	1-1.250	126.25	3207	112.00	2845	39.00 991 24.75 629 11500 5216
D42E265	265	42	5	1-1.250	132.25	3359	118.00	2997	45.00 1143 24.75 629 12700 5761
D42E360	360	42	5	1.250-1.375	157.00	3988	141.00	3581	45.00 1143 29.50 749 15500 7031
D50E360	360	50	5	1.250-1.375	165.00	4191	149.00	3785	53.00 1346 29.50 749 15900 7212
D50F525	525	50	6	1.375-1.625	173.00	4394	155.25	3943	53.00 1346 32.00 813 22000 9979
D60F525	525	60	6	1.375-1.625	183.00	4648	165.25	4197	63.00 1600 32.00 813 23100 10478
DH30E200	200	30	5	1-1.250	126.25	3207	112.00	2845	39.00 991 24.75 629 10000 4536
DH36E200	200	36	5	1-1.250	126.25	3207	112.00	2845	39.00 991 24.75 629 11600 5262
DH36E250	250	36	5	1-1.250	126.25	3207	112.00	2845	39.00 991 24.75 629 11500 5216
DH42E250	250	42	5	1-1.250	132.25	3359	118.00	2997	45.00 1143 24.75 629 12700 5761
DH42E350	350	42	5	1.250-1.375	157.00	3988	141.00	3581	45.00 1143 29.50 749 15500 7031
DH50E350	350	50	5	1.250-1.375	165.00	4191	149.00	3785	53.00 1346 29.50 749 15900 7212
DH50F500	500	50	6	1.375-1.625	171.63	4359	153.50	3899	53.00 1346 33.00 838 22000 9979
DH60F500	500	60	6	1.375-1.625	182.38	4632	164.13	4169	63.00 1600 33.00 838 23100 10478

American Block reserves the right to change dimensions at any time without notice
 Sheave size can vary to meet customer requirements